

Column Capacity Comparison Chart for 1.8E Parallam® PSL

ALLOWABLE AXIAL LOAD (lb) FOR 1.8E PARALLAM® PSL^[1]

Column Bearing Type	Effective Column Length	1.8E Parallam® PSL Column Size														
		3 1/2" x 3 1/2"			3 1/2" x 5 1/4"			3 1/2" x 7"			5 1/4" x 5 1/4"			5 1/4" x 7"		
		100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%
On Column Base	7'	8,735	9,140	9,370	13,105	13,710	14,060	17,475	18,280	18,745	30,010	32,545	34,030	40,000	40,000	40,000
	8'	7,265	7,550	7,715	10,900	11,325	11,570	14,535	15,100	15,425	26,650	28,490	29,555	35,530	37,985	39,410
	9'	6,115	6,320	6,440	9,170	9,480	9,660	12,225	12,640	12,880	23,475	24,835	25,620	31,300	33,115	34,165
	10'	5,200	5,355	5,445	7,800	8,035	8,170	10,400	10,715	10,895	20,660	21,695	22,290	27,545	28,925	29,725
	12'	3,885	3,980	4,030	5,825	5,965	6,050	7,765	7,955	8,065	16,160	16,805	17,175	21,545	22,405	22,900

[1] Parallam® PSL allowable loads are based on solid, one-piece member.

ALLOWABLE AXIAL LOAD (lb) FOR SPRUCE-PINE-FIR NO. 2, SOUTHERN PINE NO. 2, AND WEYERHAEUSER FRAMER SERIES® BUILT-UP COLUMNS^{[1][2]}

Column Bearing Type	Effective Column Length	Spruce-Pine-Fir (SPF) No. 2 Column Size														
		(2) 2x4			(3) 2x4			(4) 2x4			(2) 2x6			(3) 2x6		
		100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%
On Column Base	7'	2,485	2,570	2,620	5,455	5,810	6,015	7,775	8,180	8,420	3,825	3,965	4,045	9,360	10,055	10,460
	8'	2,025	2,080	2,115	4,685	4,930	5,070	6,540	6,830	6,995	3,125	3,220	3,270	8,165	8,650	8,925
	9'	1,675	1,710	1,735	4,025	4,200	4,300	5,545	5,760	5,885	2,590	2,655	2,690	7,085	7,425	7,620
	10'	1,400	1,430	1,445	3,475	3,605	3,680	4,750	4,910	5,005	2,175	2,220	2,245	6,150	6,395	6,535
	12'	1,020	1,035	1,040	2,640	2,715	2,760	3,580	3,680	3,735	1,585	1,610	1,620	4,690	4,830	4,910
Column Bearing Type	Effective Column Length	Southern Pine (SP) No. 2 Column Size														
		(2) 2x4			(3) 2x4			(4) 2x4			(2) 2x6			(3) 2x6		
		100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%
On Column Base	7'	2,430	2,515	2,565	5,260	5,600	5,795	7,385	7,795	8,030	3,765	3,910	3,990	9,280	9,945	10,330
	8'	1,985	2,040	2,075	4,515	4,755	4,895	6,245	6,535	6,705	3,085	3,180	3,230	8,060	8,530	8,795
	9'	1,645	1,685	1,705	3,880	4,060	4,160	5,320	5,535	5,665	2,560	2,625	2,660	6,980	7,315	7,505
	10'	1,380	1,405	1,425	3,355	3,490	3,565	4,570	4,740	4,835	2,150	2,195	2,220	6,055	6,300	6,440
	12'	1,005	1,020	1,030	2,560	2,640	2,690	3,465	3,570	3,630	1,570	1,595	1,610	4,625	4,765	4,845
Column Bearing Type	Effective Column Length	Weyerhaeuser Framers Series ^{®[3]}														
		(2) 2x4			(3) 2x4			(4) 2x4			(2) 2x6			(3) 2x6		
		100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%	100%	115%	125%
On Column Base	7'	3,540	3,680	3,760	7,495	8,045	8,365	10,770	11,470	11,835	5,515	5,735	5,855	13,175	14,230	14,845
	8'	2,910	3,005	3,055	6,530	6,920	7,140	9,205	9,660	9,920	4,530	4,675	4,755	11,610	12,355	12,780
	9'	2,420	2,485	2,520	5,670	5,950	6,110	7,870	8,205	8,395	3,765	3,865	3,915	10,145	10,675	10,970
	10'	2,035	2,080	2,105	4,930	5,140	5,260	6,775	7,030	7,175	3,165	3,235	3,275	8,850	9,235	9,450
	12'	1,490	1,515	1,525	3,785	3,910	3,980	5,150	5,305	5,395	2,315	2,350	2,370	6,800	7,010	7,130

[1] SPF No. 2, SP No. 2, and Weyerhaeuser Framers Series® allowable loads are based on built-up sawn members nailed together as prescribed by 2024 NDS® Section 15.3.3; K_r factor of 0.6 applies.

[2] Per NDS®, each nail must penetrate all plies of column to achieve tabulated values.

- For example: 4 1/4" long (30d) nails required for 3-ply columns, 6" long 60d nails required for 4-ply columns.
- Shorter nails may reduce allowable loads and are not permitted.

[3] Weyerhaeuser Framers Series® 2x4's are MSR 1650 Grade and 2x6's are M-12 Grade per [LB-4020](#).

General Notes

- Table based on:
 - 2024 NDS®.
 - Dry use conditions.
 - Bracing in both directions at column ends.
 - Free standing columns (no exterior wall applications) with axial loads only.
- Tables are based on column sitting on a steel base. If column sits on a wood plate, loads must be checked against plate crushing
- Allowable axial loads for 1.8E Parallam® PSL have been calculated to accommodate the worst case of the following eccentric conditions: 1/6 of the column thickness (first dimension) or 1/6 of the column width.
- Allowable axial loads for SPF No. 2, SP No.2, and Weyerhaeuser Framers Series® built-up columns have been calculated to accommodate the following eccentric condition: 1/6 of the column width (parallel to the wide face of the lumber).

Some products may not be available in your region. Contact your Weyerhaeuser representative for product availability.

Additional care is required for built up columns due to code required fastener penetration, spacing, and size.